

Specifications

Capacities

| Item | | | Capacity | Recommended Lubricants | |
|--------------------------|-------------------|---------------------|------------------------|---|--|
| Fuel (approximate) | | | 60 liters (15.9 gals.) | — | |
| Engine oil | Non-turbo | 2.4 liters engine | Oil pan | 4.0 liters (4.2 qts.) | Engine oil displaying EOLCS certification mark or conforming to the API classification SJ ECU, SJ/CD ECU |
| | | | Oil filter | 0.3 liter (.32qt) | |
| | 2.0 liters engine | Oil pan | 3.8 liters (4.0 qts.) | | |
| | | Oil filter | 0.5 liter (0.5 qt.) | | |
| | Turbo | Oil pan | 4.0 liters (4.2 qts.) | | |
| | | Oil filter | 0.3 liter (.32 qt.) | | |
| Oil cooler | | 0.1 liter (.11 qt.) | | | |
| Power steering | | | 0.9 liter (.95 qt.) | Automatic transmission fluid "DEXRON II" | |
| Automatic transaxle | Non-turbo | 2.4 liters engine | 6.1 liters (6.4 qts.) | DIAMOND ATF SP II or DIAMOND ATF SP II M | |
| | | 2.0 liters engine | 8.6 liters (9.1 qts.) | | |
| | Turbo | | 6.7 liters (7.1 qts.) | | |
| Manual transaxle | Non-turbo | 2.0 liter engine | 2.0 liters (2.1 qts.) | TEXACO MTX FLUID FM | |
| | | 2.4 liters engine | 2.0 liters (2.1 qts.) | API classification GL-4, SAE 75W-90 or 75W-85W | |
| | Turbo | FWD | | | |
| | | AWD | 2.2 liters (2.3 qts.) | | |
| Transfer | | | 0.5 liter (.53 qt.) | | |
| Differential (rear axle) | | | 0.85 liter (.90 qt.) | API classification GL-5 or higher Above -10 °F (-23 °C) SAE 90, 85W-90, SOW-90 From -30 F (-34 X) to -10 F (-23 C) SAE SOW, 80W-90 Below -30 F (-34 C) SAE 75W | |

Front-wheel drive cars All-wheel drive cars :
Include 0.65liter (.69qt.) in reserve tank.